




DIMENSIONS:

9"(W) x 12"(H) x 6"(D)



LWA-20-WW-WH LWA-20-CW-WH

LED CUTOFF & ADJUSTABLE WALL PACK

Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas. Great for use with motion sensors or other instant on/off controls.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 20W
- Input current: 0.3A Max
- Other wattages: 12W, 30W, 50W, 80W, 120W
- Power factor: >0.95

HOUSING SPECIFICATIONS:

- Die-cast aluminum with powder coat finish (White)
- Operating temperature: -4°F ~ 104°F
- Lifespan: 50000 Hrs.
- IP rating: IP65, Wet Locations
- High light transmittance, anti-UV and fire resistant PC lens

CERTIFICATIONS: UL, DLC



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LWA-20-CW-WH	20W	120~277V AC	2200 LM	5000K
LWA-20-WW-WH	20W	120~277V AC	2000 LM	3000K

LIGHTING SPECIFICATIONS:

- LED type/brand: SMD 3030/ Philips Lumileds LEDs
- Total lumens: 2000 LM and 2200 LM
- Color temperature: 3000K / 5000K
- Color rendering index: >80
- Beam angle: 80° x 100°

WARRANTY: 5 years

