



- RDL4-BF-27K**
- RDL4-BF-30K**
- RDL4-BF-35K**
- RDL4-BF-41K**
- RDL4-BF-50K**
- RDL4-BF-30K-ORB**

**LED DOWNLIGHTS (BAFFLE TRIM) - 4" ROUND**

Isolated driver for improved thermal management.

**ELECTRICAL SPECIFICATIONS:**

- Voltage: 120VAC
- Wattage: 10W
- Power factor: >0.9
- Efficacy: 65LM/W, 68LM/W, 72LM/W, 74LM/W, 76LM/W

**HOUSING SPECIFICATIONS:**

- Die-cast aluminum with white powder coat finish (oil-rubbed Bronze Finish available in 3000k)
- Gasket: closed cell Neoprene foam gasket
- Isolated driver for improved thermal management
- Suitable for damp locations when gasket is used
- Maximum Ambient temperature: 104°F

**CERTIFICATIONS: UL**



**DIMENSIONS:**

**4" DIAMETER**

**ACCESSORIES:**



Includes medium base E-26 screw-in adaptor that fits any standard incandescent downlight

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
RDL4-BF-27K	10W	120VAC	650 LM	2700K
RDL4-BF-30K	10W	120VAC	680 LM	3000K
RDL4-BF-35K	10W	120VAC	720 LM	3500K
RDL4-BF-41K	10W	120VAC	746 LM	4100K
RDL4-BF-50K	10W	120VAC	761 LM	5000K
RDL4-BF-30K-ORB	10W	120VAC	680 LM	3000K

**LIGHTING SPECIFICATIONS:**

- Dimming: dimmable
- Lens: 0.125" white translucent foam acrylic
- LED: EPISTAR chip (COB) and driver— 35,000-hour design life
- Total lumens: 650LM/680LM/720/746LM/761LM
- Color temperature: 2700K/3000K/3500K/4100K/5000K
- CRI: 90

**WARRANTY: 5 years**

