

SPECIFICATION SHEET: WH4-120-L

This Is An Original Product From Fulham Co., Inc

Description: WorkHorse Series Versatile, Solid State Electronic Ballast. Small Case Size,


High Power Factor, Light Weight, Available In 120/230/277V 50/60 Hz.

This Ballast Will Operate Following Lamps.

F21T5/F28T5

ELECTRICAL DATA

INPUT VOLT: 120V ± 10%, 50/60	Hz									
LAMP WATTS/TYPE	F21T5	F28T5	F35T5	-	-	-	_	-		
LAMPS OPERATED	2	2	2							
INPUT WATTS	42	52	51							
LINE CURRENT:	0.38	0.46	0.45							
POWER FACTOR	0.94	0.95	0.95							
BALLAST FACTOR	0.85	0.82	0.66							
EFFICACY FACTOR	2.01	1.57	1.30							
THD	34.9%	32.4%	30.7%							
EMI/RFI COMPLIANCE	FCC PART 18-A(non-Consumer)									
SOUND RATING	" A "									
BALLAST TYPE		INSTANT START								
VOLTAGE TRANSIENTS		ANSI 62.41								
INPUT/PROTECTION			FUSE							
MINI. LAMP START		SEE LAMP SPECS								
MIN. BALLAST OPERATING TEMP		-30 °C (-20 ° F)								
MAX. CASE TEMP	70 °C (158 ° F)									
ENERGY STAR 4.0	-									
APPROVALS/CLASS	UL /cUL LISTED, CLASS " P ", 1 OR 2 OUTDOOR									



WIRING DIAGRAMS											
WRE	BLACK	WHITE	RED	BLUE	YELLOW	BROWN					
LENGTH - INCHES	12 <u>+</u> 1"	12 <u>+</u> 1"	36 <u>+</u> 1"	-	36 <u>+</u> 1"	-					

FOR WIRING DIAGRAM,
PLEASE REFER TO FULHAM'S CATALOG

NOTE : This Ballast Must Be Grounded

Fulham Co., Inc extends limited warranty only to the original purchaser or to the first user for the period of <u>5 years</u> from the date of manufacture as indicated by the date code stamped on each product and when properly installed and under normal conditions of use. For additional warranty guide line, please refer to our Complete Product Catalog OR <u>call Customer Service at 1-323-599-5000</u>.

Due to a program of continuous improvement, fulham Co., inc reserves the right to make any variation in design or construction to the equipment described.